

## PC/104+ Peripherals



Type	<b>MSME104+</b>	<b>MSMS104+</b>	<b>MSMG104+</b>
Function	LAN PC/104-Plus	SCSI PC/104-Plus	Framegrabber PC/104-Plus
Controller	i82559	AIC-7860	BT848A
Connector	100/10BASE-T	SCSI	3 x Coax
Bus	PCI	PCI	PCI
Onboard Flash (MB)	32k BIOS	32k BIOS	—
Remarks	—	—	—
Power Normal	3.3/5V	3.3/5V	3.3V
Power Suspend	3.3/5V	3.3/5V	3.3/5V
Operating Temp.	-25°C to +70°C	-25°C to +70°C	-25°C to +70°C
Extended Temp.	-40°C to +85°C	-40°C to +85°C	—
Weight (gr)	90	80	80
MTBF	> 100'000 h	> 100'000 h	> 100'000 h



Type	<b>MSMJ104+</b>	<b>MSMW104+</b>	<b>MSMVA104+</b>
Function	PC-Card/PC/104-Plus	FireWire PC/104-Plus	XVGA PC/104-Plus
Controller	TI1450	Texas, IEEE 1394	ATI M7-CSP 32MB
Connector	PCCard	2x FireWire	2x CRT, LVDS, DVI, TV-out/In
Bus	PCI	PCI	PCI
Onboard Flash (MB)	—	—	64kB BIOS
Remarks	—	—	—
Power Normal	3.3V	3.3V	3.3V
Power Suspend	3.3/5V	3.3/5V	3.3/5V
Operating Temp.	-25°C to +70°C	-25°C to +70°C	-25°C to +70°C
Extended Temp.	-40°C to +85°C	—	—
Weight (gr)	90	80	80
MTBF	> 100'000 h	> 100'000 h	> 100'000 h

All data subject to change without notice.

**Sales**

P: 858-490-0597

F: 858-490-0599

[sales@adlogic-pc104.com](mailto:sales@adlogic-pc104.com)

**Advanced Digital Logic**

P: 858-490-0597

4411 Morena Blvd., Suite 101

San Diego, CA 92117

[general@adlogic-pc104.com](mailto:general@adlogic-pc104.com)

**Technical Services**

P: 858-490-0597

F: 858-490-0599

[tech@adlogic-pc104.com](mailto:tech@adlogic-pc104.com)